


# CUNDALL




## **HKAEE: Technical Forum 2014**

*High Performance Building Design  
Going Beyond Green Ratings and  
Designing Buildings that Perform*



## Sustainability

- Strategic Sustainability Consultancy
- Sustainable master-plans
- Green Building Certification
  - LEED
  - HK BEAM Plus
  - China Green Building Label (3-Star)
- Microclimate simulation & analysis
- Renewable and Low Carbon Technology
- Water resources



## Building Performance

- Portfolio strategic improvement planning
- Operational Performance Audit – Energy, Water, Waste, IEQ
- BMS fine tuning/ Building optimization
- Re-commissioning
- Building Upgrade implementation, Design & PM services
- Asset Condition Assessment



## Building Services

- Low energy building design
- Building Services (Mechanical, Electrical, Plumbing and Drainage, Fire Services)
- Data Centre & Critical system specialists + CFD
- Advanced system design (chilled beams, natural ventilation etc.)
- Building Information Modelling (BIM)



# High Performance Buildings

CUNDALL



Hong Kong Science & Technology Park  
– Phase 3



Children's Hospital, Hong Kong



Yau Ma Tei Police Station, Hong Kong



Eaton Hotel Chiller Upgrade  
Gold Award Hong Kong Awards for  
Environmental Excellence 2013



Mixed-use Development, Kunming  
Low Energy mixed mode office tower



DFS Global Retail Portfolio  
Global Energy Conservation  
Green Design New / Refurb Guidelines


**"HK3030"**  
**Target Reduction 30% Electricity Consumption**  
**in Buildings by 2030** (Baseline: Year 2005)

HKGBC Roadmap (Dec 2012)

Excellent plan for demand side management of Hong Kong's buildings which consume 90% of our electricity




## 3030 target is 60% reduction from BAU



Arup

“Aggressive but achievable target”

**60% reduction requires a full range of measures but we need to start now and move quicker!**



- **BEC 2012 released**
- **Compulsory Audits but no actions required**
- **Government is building greener**
- **HKGBC EUI Benchmarking Tool under development**
- **BEAM v1.2 rapidly increasing market uptake of Green Building Assessments**

**Momentum in Hong Kong is strong**

## **WE NEED TO ASK**

- **HOW CAN WE GO for 30-50% Savings TODAY?**

**For NEW and EXISTING BUILDINGS**

The HK3030 Campaign takes a 'carrot-and-stick' approach to reduce electricity level in all building types in Hong Kong, including the existing building stock which has traditionally been the most challenging. HK3030 puts forward solid recommendations to expand the scope of regulatory control to push for more green buildings, and to incentivise the market for optimal outcomes

## HKGBC supporting government


- Public Education - HK3030 Charter Programmes
- Developing a credible and territory-wide online benchmarking tool and labelling scheme on building energy performance;
- Developing a suite of tools under the current BEAM Plus Standard
- Research and Professional Training for the Industry

## HK3030 Recommends **POLICY INITIATIVES**


- Regulatory Control enhancement
- Incentive suggestions & Funding support
- Lead by example - Building Green & Renting Green
  - **Take the lead by adopting EUI performance standard which shall be more stringent than BEAM Plus rating and publishing the performance of the public sector buildings**




## Building Lifecycle




## Green Building Rating Systems generally consider Design & Construction Stage only



## Setting an operational EUI target influences the whole building lifecycle




Energy Modelling is a comparative analysis looking at % reduction operating under the same schedule of operation



**Baseline**  
**(code compliant)**

vs



**As Designed**

Energy Modelling result = % reduction under standard operational parameters  
e.g 8am to 7pm, average occupancy, average loads

Actual buildings do not operate under uniform operation or ideal scenarios.

Tenants have different operational profiles and demands so part load performance is highly variable and the ability to deal with this is not measured by energy models

## Usage = Demand x Efficiency x Control

To get big savings we must reduce Demand significantly and focus on how to optimise and control the systems particularly in low load part load conditions

### Reduce demand

- Passive design
- CO2 demand control
- Reduce the AC footprint
- ↓ Exhaust air make-up



### Efficiency

- Optimise for part load efficiency
- Address issues of oversizing and ability to turn down at part load.
- Energy efficient equipment standard.

### Control & Optimisation

- Switching off = most efficient
- Modularise and enable part load performance
- Advance monitoring and controls
- Monitor, Measure in real time. Remote analysis

## Buildings are very energy intensive

1. Hot /Humid Climate demands AC
2. Long Operating Hours
3. Densely occupied buildings
4. Everything is on all the time
5. Monitoring is not common or limited
6. Low energy costs (compared to other costs)
7. Energy is invisible and intangible



Typical Grade A office

- Centralised Chiller Plant
- Typically VAV AC
- 500+ lux Lighting
- BMS & Dedicated Building Manager
- Large AC footprint
- Large Lobby



Typical Grade C office

- Split AC COP 2.5
- Lighting by Tenant
- No BMS
- No AC to corridors, lift lobbies or toilets
- Small lobby

# Centralised vs Decentralised AC




Typical Grade A office

~50% Avg. Savings  
Whole Building  
Energy  
Consumption



Typical Grade C office

Energy EUI kWh/m<sup>2</sup>/m<sup>2</sup>



Data source : William Chung , Y.V. Hui (2009) (EUI MJ/m<sup>2</sup> converted to kWh/m<sup>2</sup>)  
A study of energy efficiency of private office buildings in Hong Kong  
Department of Management Sciences, City University of Hong Kong, Kowloon Tong, Hong Kong





Typical Grade A office

## Typical Grade A office

Everything ON during long business hours

Over Provisions (Must have spare capacity everywhere)

Large systems and oversizing -  
Systems can't turn down properly

**Why?**



Typical Grade C office

## Typical Grade C office

Modular AC on when the tenant wants to use it off when not needed.


The tenant controls the temperature and fan speed and pays for the bill.

Tenant adds extra provisions if they need


# Impact on Designing to a brief with overprovisions

## Macau Hotel Consumption:

- 735kWh/m<sup>2</sup> per year
- Double the energy of similar hotels operated by the same hotel group



Energy Use General Breakdown



	kWh	kWh/m <sup>2</sup> AC Area	%
<b>HVAC</b>	6,556,289	366	50%
<b>Lighting</b>	2,447,935	137	19%
<b>Hot Water</b>	736,240	41	6%
<b>Lift</b>	541,725	30	4%
<b>Kitchen Equipments</b>	1,105,557	62	8%
<b>Miscellaneous</b>	1,771,668	99	13%
<b>Total</b>	13,159,414	735	100%


- Drastically oversized (ventilation, exhaust, AC etc)
- High Exhaust and Fresh air ventilation rate (spa, restaurant, kitchen)
- Combined Kitchens Exhaust 100% on / off
- Lack of Chiller plant pumping controls
- Intensive halogen lighting
- Simultaneous Heating & Cooling risk in winter

## Key Recommendation

- Rebalance Exhaust and Fresh Air Make up
- Add VSD controls and dampers to Exhaust & Make-up
- Add VSD Chiller plant pumping controls
- Replace Halogen with LED MR 16 fitting

**> 30% energy  
wasted due to  
overprovisions**

**Exhaust  
oversized & no  
controls for  
partload**



## Why do we oversize?

- Cater for all possibility and deal with the unknown
- Design briefs require it
- To cater for plant & equipment degradation
- Provide future spare capacity
- Easier & less risk than not oversizing

We oversize to provide long term capacity but this results in overprovisioning and affects the part load performance at which most buildings operate.

There are some good reasons why we do it but we could do it better by allowing for future capacity to be added later and/or built in such a way it can allow for

We need to carry out a right sizing approach

- Design Briefs & standard design oversize everything

## Oversizing impacts poorly on

VAV AC systems  
VSD Fans – Turndown limited  
VSD Pumps – Turndown limited  
Large chiller plants – Capex wasted  
Lighting without dimming control

## Oversizing is Good for

Cooling Towers – Improves performance  
Ductwork – Lower pressure low energy  
Cooling Coils – Allows for degradation  
Oil Free chillers – Better at part load  
Lighting with dimming control

- Right sizing recognizes where we need to focus on optimising the systems
- Right sizing also requires rebalancing or re-commissioning once in operation, so it can be done during the operational phases as well.
- Right sizing takes time and extra effort but is a valuable exercise

Many Design briefs lead to overprovisions, we need to either challenge them or consider more practical and efficient ways to achieve the same objectives

Low Energy Buildings still have

- Spare capacity
- Supplementary systems


Design Briefs should also include

- EUI operational energy targets (kWh/m<sup>2</sup>)
- Requirements for Passive design (Daylight & Energy performance)
- Low Energy Design Brief (e.g. Lighting, Fresh Air)
- Right Sizing & Design for Efficient Part Load
- Commissioning to go beyond T&C and rebalance the systems
- Ongoing fine tuning and optimization to be specified at end of Defects Period

## BEAM Plus Platinum & EUI target

Emphasis on demand reduction, monitoring and controls, operational fine tuning

- Passive design OTTV 10 W/m<sup>2</sup>
- Total Heat Recovery
- CO2 Demand dependent fresh air control
- All LED office lighting 350-400lux
- Real time web energy monitoring for landlord & tenants
- Energy model calibrated to set operational targets for fine tuning
- Tenant fitout guideline and engagement process
- Real time public display of performance and savings





## Demand Side

- Passive Design WWR<40% with shading
- Reduce Lux levels, add task lighting
- CO2 fresh air demand control
- Heat recovery & VSD exhaust control



## Efficiency


- LED lighting office lighting <6W/m<sup>2</sup> designed for 350-400 lux
- Oil Free Chiller and optimized plant (12W)
- Free Cooling & Natural Ventilation modes

## Control & Monitoring


- 100% Dimmable office lighting with Daylight & Occupancy Sensors
- Advanced BMS Control optimisation on air side and water side controls
- Modular AHU for VAV and Modular DC fan coil for SME small offices
- Real time Energy monitoring for Landlord, Tenant and Public

## Demand Side

- Reduce Lux levels, add task lighting
- Apply light where it is needed



Blanket



Task



## Efficiency

- LED lighting is now more efficient for most applications
- HKSP are using CREE latest 100lm/W fittings



## Control

- All fittings are dimmable and can be adjusted for use with task lighting
- Daylight & Occupancy sensors are used throughout
- Basic control is to switch off when not in use




- Integrated Plant Control
- VSD on Chilled Water Pumps
  - Variable Primary Flow
  - Variable Secondary Flow
- VSD on Condenser Water Pumps
- VSD on Cooling Towers Fans

Chiller Plant replacement can target 40% savings

Total Plant inc pumps	Air Cooled chiller	Std Water Cooled	District Cooling	VSD pumps Std Chiller	VSD pumps + Oil Free
kW/Tr	1.2-1.5	0.8-1.0	0.75-1.1	0.65-0.75	0.5-0.65



## Building Energy Monitoring

- Submetering and real time energy monitoring
- Tenant interface and monitoring
- Public display of Performance and saving



## Advanced Control

- Total Chiller Plant COP optimisation
- CO2 Demand control Ventilation
- Heat Recovery & VSD exhaust interlock
- Fully Dimmable LED lighting
- Mixed Mode AC with Free cooling & Nat Ventilation modes



## Public Display

EPMS Display Endpoints at Main Entrance Lobby of 12W, 15W and 16W

Media streaming controller at IT Riser Room



Landlord Control & real time access via web / Smartphone

## Tenant Web/ Smartphone interface



Tenant's PC (HKSP Intranet)



Internet Link



BMS Server



EPMS Database servers at HKSP P1&P2 Main IT Room



Web base administration client of EPMS



Smart Phone Apps development workstation



EPMS content management and streaming servers at HKSP P1&P2 Main IT Room

— IT Flow  
- - - BMS Flow


## BEAM Plus Platinum & EUI target

Designed to target > 40% savings

- Reducing Demand
- Optimising efficiency
- Controls & monitoring

Operational target is reliant upon

- Tenant design review and operational co-operation
- Continual monitoring and improvement (tenant & landlord)
- Tenant behavior influence to reduce demand on services
  - Tenant Energy reviews
  - 24-26 °C set points during Summer
  - Education on use of mixed mode AC




- **Set EUI Operational target for savings**
  - Aim for 40-60% Savings over Benchmarks
  - Change the process from design focused to operational
- **Reduce Demand**
  - Reduce the AC footprint and lighting demands
  - Passive design and
- **Right Size and Rebalance for actual operation**
  - Carry out a right sizing review
  - Recognise we will still oversize and allow to rebalance
- **Modularise AC systems**
  - Advanced HVAC = smaller systems we can switch off / modulate
- **Employ advanced controls & monitoring**
- **Rebalance and Re-commission when occupied**

# Focus – Existing Building





## Target requires most savings from existing buildings




## Strategic approach to Energy Retrofits

- Investigation Energy Audit (2011)
- Key Recommendations
  - Global 5 year strategies
  - Baseline and Energy Savings Target
  - Green Design guidelines for refurbishment projects
  - Global and local energy metering
  - Global LED lighting upgrades – mostly during refurbishment
  - Key initiatives for major stores


## Energy Audit (2011)




## Project Locations




## Global System Architecture



Energy Utilization Index (kWh/sqm/year) Class 1



Energy Utilization Index (kWh/sqm/year) Class 2



Energy Utilization Index (kWh/sqm/year) Class 3




# 5 Phase Energy Saving Upgrade Plan

CUNDALL

2010	2011-13	2014/15	2016	2017	2018
	Phase 1	Phase 2	Phase 3	Phase 4	Phase 5
Savings Target	10%	8%	5%	4%	3%
Cumulative	10%	18%	23%	27%	30%
ROI	4.2	3.9	6.5	7	8

## Global Action Plan - Net Present Value of the Investment



**Phase 1 has achieved >10% Savings and ROI<4 years**

**Phase 2 being commenced now with buy-in from Senior Management**

## **Key Initiatives**


- Retail LED lighting upgrades achieving 20-30% reduction
- Cooling & HVAC plant reduction + chiller upgrades
- Enhance Monitoring & control
- Efficient equipment savings to offset increase technology
  
- Green Design guidelines for new & refurbishment projects
- Global and local energy & water metering
- Global LED lighting upgrades – mostly during refurbishment
- Chiller Plant Replacement
- BMS & Controls upgrades

- **Benchmark your performance & carry out a deep dive energy audit and request options to savings over a phased approach**
- **Use savings to fund each next phase**
- **Set EUI target for savings Aim for 30-40% savings**
- **Install real time energy monitoring**
- **Rebalance Systems to optimize performance**
- **Add controls and VSDs (Variable Speed Drives)**
- **Replace Chiller plants near end of life with high efficiency chiller and all VSD controls**
- **Replace Lighting with LED and controls**
- **Fine tune and continually optimise**

**It takes time and effort but done properly will easily pay for itself**



- **We need to act now**
- **Design / Retrofit with an operational focus**



- **Set more ambitious targets to go >30% savings**
- **Reduce demand, challenge design briefs and focus on controls and optimisation**
- **Plan a program for Retrofitting our buildings**
- **Embrace the HK 3030 Challenge**

Thank You